KYOCERa

TASKalfa 2554ci

As one of the most reliable products in the field, the TASKalfa 2554ci is designed to operate in dynamic work environments and ensure consistent productivity. This device offers user-friendly operations, advanced security and highly productive intelligent features. Sharp black text and high impact colour output with an exceptional range of scanning, input and professional finishing options will help your business focus on what matters. The 10.1 inch touchscreen with its new simple, intuitive and efficient user interface will make operating this device smooth and easy.



Outstanding Image Quality

The TASKalfa 2554ci gives you incredible image quality and outstanding colors with high resolution and superior image processing.



Delivers realistic image with high resolution

Provides printing resolution of 1,200dpi. You will enjoy sharp, detailed print results even in fine lines and small characters, giving your image a bright and vivid impression along with the realistic texture.

Impressive quality even for repeated copies

Reduces the color difference with accurate color matching when digital copying, and also avoids quality degradation during repeated photocopying.

Stable print quality





The 1st page The 1000th page

Keeps the stability of color performance, no matter for the $1^{\rm st}$ page or the $1,000^{\rm th}$ or more.

Beautiful contrast



Provides a better contrast with incredible deep blacks.

High gloss



Existing model

New model

Performs a glossy finishing on images.

			TASKalfa 2554ci
			Main Specifications
Main Function			Copy, Print, Scan, Fax (Optional)
Writing Method			Semiconductor Laser
СРИ			ARM A53 1.6GHz
Print Speed (A4) (Mono/Color)			25/25 ppm
Scanning Speed (A4) 300dpi	DP-7140	Simplex	50 ipm
		Duplex	16 ipm
Scanning Speed (A4) 300dpi	DP-7150	Simplex	80 ipm
		Duplex	48 ipm
Scanning Speed (A4) 300dpi Dual Scan		Simplex	100 ipm
	DP-7160	Duplex	200 ipm
Scanning Speed (A4) 300dpi Dual Scan with Duplex Feed Detection DP	DP-7170	Simplex	100 ipm
		Duplex	200 ipm
Memory			Standard 4GB (Max. 4GB)
SSD/HDD Capacity			SSD 32GB (Standard) / HDD 320GB or 1TB (Optional)
Stable Time (From the mainpower ON)			18 seconds
Paper Capacity	Standard		2 x 500 sheets (Cassette) + 150 sheets (MPT) (A4 / Letter size or less equivalent to 80 g/m2) 2 x 600 sheets (Cassette) + 165 sheets (MPT) (A4 / Letter size or less equivalent to 64 g/m2)
	Maximum		7,150 sheets (Main Unit + 2 x 1,500 sheets PF-7150 x1 + 3,000 sheets PF-7120 x1 + MPT)
	Cassette		Min. A6R - Max. SRA3(320mm x 450mm); Cassette 1 Min. A6R – Max. A4R (Legal)
Paper Size	MPT		Min. A6R - Max. SRA3(320mm x 450mm) & Banner Print (1,220mm x 304.8mm)
Paper Weight	Cassette		52~300g/m2
	MPT		52~300g/m2 ; Banner paper 136~163g/m2
Duplex Printing			Paper size: Min. A6R - Max. SRA3(320mm x 450mm) ; Paper weight: 60~256g/m2
Output Capacity			Max. 500 sheets + 100 sheets face-down with Inner Job Separator
Control Panel			10.1 inch resistive touch panel
Dimension (W x D x H) (Main Unit)			602mm x 665mm x 790mm
Weight (Main Unit)			Approx. 90 kg
Power Consumption (Standard configuration)	Copy/Print Mode		450W
	Stand-by Mode		40W
	Energy Saver		0.5W
Noise (ISO7779/ ISO9296)	Copy/Print Mode (Mono/Color)		66dB/67dB
	Stand-by Mode		35dB
			Copy Functions (Standard)
Copy Size			Max. A3 (Ledger) - Min. A6R (StatementR)
Resolution			Scanning: 600 x 600 dpi ; Writing: 1200 x 1200 dpi multiple value
First Copy Time (Mono/Color)			6.4/8.5 seconds
Zoom Ratio Manual			25% - 400% (1% per Step)
Multiple Copy			1 - 9,999
			Print Functions (Standard)
Resolution			1,200 x 1,200 dpi ; 4,800 equivalent x 1,200 dpi level
PDL & Emulation			PRESCRIBE, PCL6 (PCL-XL, PCL 5c), KPDL3 (Postscript 3 compatible), XPS, OpenXPS, PDF Direct Print Ver. 2.0
First Print Out Time (Mono/Color)			7.0/9.2 seconds
Supported Protocol			TCP/IP(IPv4/IPv6), Bonjour
Operating System Supported			Windows 8.1/10, Windows Server 2012/2012 R2/2016/2019, Mac OS X(10.9 \sim), Google Chrome OS
Interface			Ethernet (1000Base-T/100Base-TX/10Base-TX1, USB 3.0x1, USB Host Interface (USB Host)x4, NFC TAGx1

	Scan Functions (Standard)
Original size	Table: Max. A3 (Ledger) DP: Max. A3 (Ledger) - Min. A6R (DP-7140 is A5R) Banner: Max. 1,900mm
Resolution	600 x 600 dpi, 400 x 400 dpi, 300 x 300 dpi, 200 x 200 dpi, 200 x 100 dpi, 200 x 400 dpi
File Format	TIFF, JPEG, XPS, OpenXPS, PDF (MMR/JPG compression/High-compression PDF), wPDF/A-2, Encrypted PDF, Searchable PDF (Optional), MS Office file(Optional)
Image Type Mode	Text, Photo, Text + Photo, Text (Fine Line)
Send Method	SMB (Version 3.0), SMTP, FTP, FTPoverSSL, USB, TWAIN Source (Network), WIA Driver (Network), DFS, DSM
Address Storage	2,000 addresses (Common address list), 500 groups (Group address list)
	Fax Functions (Optional)
Original Size	Max. A3 (Ledger) - Min. A6R (StatementR), Banner: 1,600mm
Coding Method	MMR, MR, MH, JBIG
Transmission Speed	33.6 kpbs
Transmission Time	Less than 3 sec. (With JBIG)
Memory	170MB
Memory	Consumables & Options
Toner Kit	TK-8360 (C/M/Y): 12,000 pages TK-8360 (K): 25,000 pages
Maintenance Kit	MK-8335 (A/B): 200,000 pages MK-8345 (D/E): 600,000 pages
Waste Toner Bottle	WT-8500
Document Processor	DP-7150: 140 sheets RADF Type; DP-7140: 65 sheets RADF Type (TASKalfa 2554ci / TASKalfa 3554ci only); DP-7160: 320 sheets One-path Duplex Scanning Type;w DP-7170: 320 sheets One-path Duplex Scanning Type with double paper feeding detector
Paper Feeder	PF-7140: 500 sheets x 2; PF-7150: 1,500 sheets x 2 (A4/Letter); PF-7120: 3,000 sheets Large capacity side deck (A4/Letter)
Finisher	DF-7100: Inner Finisher *No support for 70ppm; AK-7110: Attachment Kit; DF-7120: 1,000 sheets Finisher; DF-7140: 4,000 sheets Finisher with 65 sheets Staple; DF-7150: 4,000 sheets Finisher with 100 sheets Staple; PH-7C: Punch Unit for DF-7120/DF-7140/DF-7150; PH-7120: Punch Unit for DF-7100; MT-730(B): 7 Bin Mailbox for DF-7140; JS-7110: Inner Job Separator; IS-7100**: Inserter Unit; ZF-7100**: Z Folding Unit; BF-730: Booklet Folder for DF-7140; BF-9100: Booklet Folder for DF-7150; SH-10: Staple for DF-7100/DF-7120/BF-730/BF-9100; SH-12: Staple for DF-7140; SH-14: Staple for DF-7150
Fax System	Fax System 12
Internet FAX	Internet FAX Kit(A)
Card Authentication	Card Authentication Kit(B)
Gigabit Ethernet Board	IB-50
Wireless LAN Interface	IB-37 (Wi-Fi 2.4 GHz/5 GHz multi-band support) / IB-38 (Wi-Fi 2.4 GHz capable) *IB-38 for Indonesia, Bangladesh only
Storage Device	HD-15: HDD 320GB, HD-16: HDD 1TB
Embedded OCR	Scan Extension Kit(A)
Banner Paper Tray	Banner Guide 10
Numeric Key Pad	NK-7120
Original Tray	DT-730 (B)
Keyboard Holder	Keyboard Holder 10



บริษัท เคียวเซร่า ด็อคคิวเม้นท์ โซลูชั่นส์ (ประเทศไทย) จำกัด

335 ถนนรัชดาภิเษก แขวงวงศ์สว่าง เขตบางชื่อ กรุงเทพฯ 10800 โทร. 0-2586-0333 โทรสาร. 0-2586-0278 www.kyoceradocumentsolutions.com/th

KYOCERA Document Solutions does not warrant that any specifications mentioned will be error-free. Specifications are subject to change without notice. Information is correct at time of going to press. All other brand and product names may be registered trademarks or trademarks of their respective holders and are hereby acknowledged. © 2021 KYOCERA Document Solutions (Thailand) Corp., Ltd.